

RUOTE LISCE

Plain rim wheels

RUOTE LISCE MONOPEZZO PER ELEVATORI

Ruote lisce per elevatori a tazze con costruzione in pezzo unico, per catena tipo DIN 764-DIN 766 e maniglioni DIN 5699 - DIN 745 o per catena tipo LH e attacchi tazze tipo ATS. Costruite integralmente in acciaio speciale con elevata resistenza all'usura; disponibile con trattamento supplementare di tempra ad induzione della superficie di appoggio della catena. Disponibile con cave periferiche per scarico polveri; foro lavorato secondo richiesta.

PLAIN RIM WHEELS FOR ELEVATORS, ONE PIECE

Plain rim wheels for bucket elevators with one piece construction, for chain type DIN 764-DIN 766 and shackles DIN 5699 - DIN 745, or chain type LH and special ATS bucket attachments. Made of special alloy steel, with high wear resistance; available with supplementary induction tempering of the area of contact with the chain. Available with peripheral relief slots for material discharge; bored and keyed according to request.

| Codice Code | Ø Primitivo Pitch line | Ø Esterno External | Catena - Chain Ø | | Dimensioni Dimensions | | | Massa Weight |
|----------------|------------------------------|--------------------------|---------------------|----|--------------------------|-----|-----|-----------------|
| | Dp | D | DIN 764 DIN 766 | LH | A | C | E | |
| | mm | mm | mm | | mm | mm | mm | kg ≅ |
| RL 10/350 | 350 | 360 | 10 | - | 16 | 60 | 70 | 35 |
| RL 10/400 | 400 | 410 | 10 | - | 16 | 70 | 80 | 48 |
| RL 13/400 | 400 | 420 | 13 | 14 | 19 | 80 | 90 | 58 |
| RL 13/500 | 500 | 510 | 13 | 14 | 19 | 80 | 90 | 85 |
| RL 16/500 | 500 | 515 | 16 | 16 | 22 | 90 | 100 | 95 |
| RL 18/500 | 500 | 520 | 18 | 16 | 23 | 100 | 110 | 110 |
| RL 20/500 | 500 | 520 | 20 | 19 | 26 | 110 | 120 | 120 |
| RL 16/630 | 630 | 645 | 16 | 16 | 22 | 95 | 120 | 165 |
| RL 18/630 | 630 | 645 | 18 | 19 | 23 | 105 | 120 | 180 |
| RL 20/630 | 630 | 650 | 20 | 19 | 26 | 110 | 130 | 195 |
| RL 23/630 | 630 | 650 | 23 | 22 | 30 | 120 | 140 | 210 |
| RL 16/710 | 710 | 715 | 16 | 16 | 22 | 95 | 140 | 220 |
| RL 18/710 | 710 | 720 | 18 | 19 | 23 | 105 | 140 | 230 |
| RL 20/710 | 710 | 720 | 20 | 22 | 26 | 110 | 150 | 255 |
| RL 23/710 | 710 | 730 | 23 | 22 | 30 | 125 | 160 | 285 |
| RL 26/710 | 710 | 730 | 26 | 26 | 35 | 140 | 160 | 305 |
| RL 20/800 | 800 | 810 | 20 | 22 | 28 | 115 | 140 | 325 |
| RL 23/800 | 800 | 810 | 23 | 22 | 30 | 125 | 160 | 365 |
| RL 26/800 | 800 | 820 | 26 | 26 | 35 | 140 | 160 | 395 |
| RL 30/800 | 800 | 820 | 30 | 30 | 41 | 150 | 170 | 415 |

